

# Nahtlose Starkwandrohre

Maschinenbau, EN 10297-1, E355  
 Stahlbau, EN 10210-1/-2, S355J2H



Abmessungen mm	
20	x 4
	5
21.3	x 4
	5
25	x 2.3
	5
	6.3
26.9	x 4
	5
30	x 4
	5
	6.3
	8
31.8	x 4
	5
	8
32	x 6
	8
33.7	x 4
	5
	6.3
	8
36	x 5.5
	8
38	x 5
	8
	10
40	x 6
	7.5
	10
42.4	x 4
	5
	6.3
	7.1
	8
	10
	12.5
44.5	x 5
	7.1
	8
	10
45	x 6.5
	8.5
	12.5
48.3	x 2.9
	4.5

Abmessungen mm	
48.3	x 5
	6.3
	7.1
	8
	10
	12.5
50	x 7
	9
	12.5
51	x 4
	5
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
54	x 5
	7.1
	10
55	x 13.5
56	x 8
	10
	14
57	x 4
	5
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
	16
60	x 17.5
60.3	x 3.6
	4
	4.5
	5
	5.6
	6.3
	7.1
	8
	10
	11

Abmessungen mm	
60.3	x 12.5
	14.2
	16
63	x 6.5
	9
	11.5
	13.5
	15.5
63.5	x 5
	5.6
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
	16
65	x 18.5
70	x 5
	5.6
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
	16
	17.5
	20
	22.5
71	x 7.5
	10.5
	13
	15.5
	17.5
73	x 10
	14.2
	16
	17.5
75	x 7.5
	9.5
	12.5
	15
	20

Abmessungen mm	
75	x 22.5
76.1	x 4.5
	5
	5.6
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
	16
	17.5
	20
80	x 8.5
	12
	15
	17.5
	20
82.5	x 4.5
	5
	5.6
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
85	x 9
	12
	15
	17.5
	20
	25
	27.5
88.9	x 4
	4.5
	5
	5.6
	6.3

# Nahtlose Starkwandrohre

Maschinenbau, EN 10297-1, E355  
 Stahlbau, EN 10210-1/-2, S355J2H



Abmessungen mm
88.9 x 7.1
8
8.8
10
11
12.5
14.2
16
17.5
20
22.2
25
90 x 9.5
11.5
13.5
17
20
27.5
30
95 x 8
10
12.5
14
16
17.5
19.5
20
22.5
25
30
100 x 7.5
10
12.5
14.5
18.5
22
32.5
35
101.6 x 4.5
5
5.6
6.3
7.1
8
8.8
10

Abmessungen mm
101.6 x 12.5
14.2
16
17.5
20
22.2
25
28
30
106 x 10.5
13
17.5
21.5
25
108 x 5
6.3
7.1
8
8.8
10
11
12.5
14.2
16
17.5
20
22.2
25
28
32
112 x 11
13.5
16
20.5
24.5
114.3 x 5
5.6
6.3
7.1
8
10
11
12.5
14.2
16
17.5

Abmessungen mm
114.3 x 20
22.2
25
28
36
115 x 40
118 x 11.5
14
19
23.5
27.5
30
121 x 7.1
8
10
11
12.5
14.2
16
20
25
30
36
40
125 x 12.5
15
17.5
22.5
27
42.5
127 x 5
5.6
6.3
7.1
8
8.8
10
11
12.5
14.2
16
17.5
20
22.2
25
28

Abmessungen mm
127 x 30
36
40
130 x 45
50
132 x 13
21
26
30.5
133 x 5
5.6
6.3
7.1
8
10
11
12.5
14.2
16
17.5
20
22.2
25
28
30
32
36
40
139.7 x 5
5.6
6.3
7.1
8
10
12.5
14.2
16
17.5
20
22.2
25
28
30
35
40
140 x 14

# Nahtlose Starkwandrohre

Maschinenbau, EN 10297-1, E355  
 Stahlbau, EN 10210-1/-2, S355J2H



Abmessungen mm	
140	x 17
	20
	25
	30
	37.5
	45
	47.5
	50
146	x 7.1
	8
	10
	12.5
	14.2
	16
	17.5
	20
	25
	30
150	x 12.5
	22
	35
	47.5
152.4	x 5.6
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
	28
	30
	32
	35
	36
	40
	45
	50
159	x 5.6
	6.3
	7.1

Abmessungen mm	
159	x 8
	10
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
	28
	30
	32
	35
	40
	45
	50
160	x 24
	35
	60
165.1	x 7.1
	8
	10
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
	28
	30
	36
	40
	60
168.3	x 5.6
	6.3
	7.1
	8
	10
	12.5
	14.2
	16
	17.5
	20
	22.2
	25

Abmessungen mm	
168.3	x 28
	30
	40
170	x 15
	26
	35
171	x 10
	12.5
	14.2
	16
	17.5
	20
	25
	30
	36
	40
	45
	50
177.8	x 5.6
	6.3
	7.1
	8
	10
	11
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
	28
	30
	35
	40
	45
180	x 15
	20
	27.5
	40
	60
190	x 15
	20
	22
	29
	42

Abmessungen mm	
190	x 50
	60
193.7	x 6.3
	7.1
	8
	10
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
	28
	30
	32
	35
	36
	40
	45
	50
200	x 20
	30
	44
	65
	70
203	x 6.3
	7.1
	8
	8.8
	10
	12.5
	14.2
	16
	17.5
	20
	22.2
	25
	28
	30
	32
	35
	40
	45
	50
212	x 21

# Nahtlose Starkwandrohre

Maschinenbau, EN 10297-1, E355  
 Stahlbau, EN 10210-1/-2, S355J2H



Abmessungen mm	
212	x 31 43.5 60
219.1	x 7.1 8 10 11 12.5 14.2 16 17.5 20 22.2 25 28 30 32 35 40 45 50
224	x 22 32 46 50 55 60
229	x 10 12.5 14.2 17.5 20 25 30 35 36 40 45 50
236	x 23 33 48 55 60
244.5	x 7.1 8

Abmessungen mm	
244.5	x 10 12.5 14.2 16 17.5 20 22.2 25 28 30 32 36 40 45 50 60 70
250	x 25 35 50 65
254	x 7.1 8 10 12.5 14.2 16 17.5 20 25 28 30 35 40 45 52 60 70
267	x 7.1 8 10 12.5 14.2 16 17.5 20

Abmessungen mm	
267	x 22.2 25 28 30 35 36 40 45 50 55 60 70 80
273	x 10 12.5 16 20 25 30 35 40 45 50 60 70 80
279	x 12.5 14.2 17.5 20 25 30 36 40 50 60 70 80
292	x 12.5 16 17.5 25 30 36 40 45

Abmessungen mm	
292	x 50 60
298.5	x 8 10 12.5 14.2 16 20 25 28 30 35 40 50 60 70 80
305	x 10 12.5 14.2 17.5 20 25 30 36 40 45 50 55 60 65 70 80 92.5
318	x 10 16 20 25 30 36 40 45 50
323.9	x 8 10 12.5

# Nahtlose Starkwandrohre

Maschinenbau, EN 10297-1, E355

Stahlbau, EN 10210-1/-2, S355J2H



Abmessungen mm
323.9 x 14.2
16
17.5
20
22.2
25
28
30
36
40
45
50
55
60
65
70
80
90
330 x 20
343 x 12.5
16
20
22.2
25
30
35
40
45
50
60
65
70
75
355.6 x 10
12.5
14.2
17.5
20
22.2
25
30
36
40
50
55
60

Abmessungen mm
355.6 x 70
80
100
368 x 10
12.5
14.2
16
20
22.2
25
28
30
35
40
45
50
60
70
80
90
100
394 x 14.2
16
20
30
35
36
40
50
55
60
70
406.4 x 10
12.5
14.2
16
20
22.2
25
30
35
40
45
50
55
60

Abmessungen mm
406.4 x 70
80
90
100
412 x 11
419 x 12.5
14.2
17.5
20
25
30
40
45
50
60
70
90
100
445 x 16
17.5
20
25
36
40
50
60
70
457 x 12.5
17.5
20
25
30
40
50
60
70
80
100
470 x 17.5
20
30
40
50
60
80
495 x 12.5

Abmessungen mm
495 x 30
40
50
100
508 x 16
20
25
30
40
50
60
70
80
100
521 x 20
40
50
559 x 14.2
20
25
30
40
50
60
80
610 x 20
25
50
60
622 x 40
50
60
100